



LIFT AND LASH (P) LTD

Polyester Flat Endless Slings:

Endless slings are the most versatile of all the web sling configurations. They can be used in all three types of hitches and the wear points can be adjusted around the circumference of the sling to increase sling life. When used in a choker or basket hitch the legs can be spread for improved load control and balance. These slings are especially used in lifting pipe bundles and used in exports. These slings can be put in the product, machines, bundles etc and go along with the product till destination, giving the most economical, safe and efficient lifting to the products



These slings can be made of any capacity , multiple ply and with fittings if required.

	WLL in Kg with one webbing sling							WLL in Kg with two webbing sling			
	Factor	Width (mm)	Straight Lift	Choker Hitch	Basket	Basket Inclination Angle		Straight Inclination Angle		Choke Inclination Angle	
			1,0	0,8	Upto 7	7-45	45-60	7-45	45-60	7-45	45-60
Violet	1000	25,50	1000	800	2000	1400	1000	1400	1000	1120	800
Green	2000	50	2000	1600	4000	2800	2000	2800	2000	2240	1600
Yellow	3000	75	3000	2400	6000	4200	3000	4200	3000	3360	2400
Grey	4000	100	4000	3200	8000	5600	4000	5600	4000	4480	3200
Red	5000	125	5000	4000	10000	7000	5000	7000	5000	5600	4000
Brown	6000	150	6000	4800	12000	8400	6000	8400	6000	6720	4800
Blue	8000	200	8000	6400	16000	11200	8000	11200	8000	8960	6400
Orange	10000	250	10000	8000	20000	14000	10000	14000	10000	11200	8000
Orange	12000	300	12000	9600	24000	16800	12000	16800	12000	13440	9600

Inspection criteria, Environmental considerations and removal criteria for flat endless slings is similar to webbing slings

A Safety Bulletin is included with every flat endless sling manufactured by us. The bulletin lists inspection information and operating practices applying to synthetic round slings.

